



Description

A precision resistance decade box suitable for a wide range of simulation work. High accuracy, long term stability, and low temperature coefficient make the 1067 ideal for simulating and calibrating precision Pt100 sensors and temperature indicators/meters that use resistive sensors.

Special care has been taken in the construction of the 1067 to ensure that the residual end resistance is as low and as stable as possible. Multiple self-cleaning silver alloy contacts are used for each position to ensure outstanding performance and long life.

Housed in a robust metal case the 1067 is fully screened and low thermal emf terminals are used. The slimline design means it takes up minimum bench space and is easily transportable.

Resistance is selected by dialling the value required using the rotary switches. This enables precise setting with a clear unambiguous indication. Each decade is scaled from 0 to 11 and therefore allows convenient overlap of the set values. The maximum value settable is 12,222.21 ohms.

Specifications

Range / Resolution	0 to 12 k Ω / 10 m Ω steps.
Number of decades	6, each decade settable from 0 to 11.
Accuracy	$\pm 0.01\%$ of setting ± 2 m Ω , after deduction of residual end resistance ± 1 m Ω for residual variation. <i>(At calibration temp of 22 °C)</i>
Residual resistance	Less than 10 m Ω . Less than 1 m Ω variation.
Power rating	0.35 watt per resistor.
Voltage Rating	Maximum 200 V DC/AC RMS.
Stability	20 ppm/year (> 1 Ω), 100 ppm/year (< 1 Ω).
Current rating	10 m Ω range: 3 A / 100 m Ω range: 2 A / 1 Ω range: 600 mA 10 Ω range: 200 mA / 100 Ω range: 60 mA / 1 k Ω range: 20 mA.
Insulation	Case to resistance terminals 2 kV / 50 Hz maximum.
Temperature coefficient	Less than 10 ppm/°C (> 1 Ω). Less than 20 ppm/°C (< 1 Ω).
Operating torque	Less than 0.1 Nm.
Contacts	Make before break – silver alloy.
Dimensions / Weight	W 355 x H 63 x D 89 mm / 1.1 kg.

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.

Features

- 10 m Ω to 12 k Ω
- 0.01 % accuracy
- Precision Pt100 simulation
- Low temperature coefficient
- In-line readout
- Excellent long term stability
- 6 digit resolution
- Fully screened

Ordering Information

1067	Precision Resistance Decade Box
C161	Traceable calibration certificate (Factory)
C114	Accredited calibration certificate (ISO 17025)