



## Description

Dry block calibrators provide a solution for calibration of RTDs, thermocouples, thermoswitches, thermistors, and other common temperature sensing devices. The 7880 and 7882 provide high performance, ease of operation and functionality to their dedicated applications. The combination of models give coverage of a wide temperature range from -100 to +700 °C (-148 to 1292 °F). The 7880 is an efficient and stable unit with dual zone technology for fast and secure cooling and heating temperature changes. Features include programmable auto stepping, stability indicator and settable min/max temperature limits for UUT damage prevention. Users can also store up to ten instrument setups with relevant criteria that can be recalled at any time.

Each model has USB communication and is EasyCal software compatible for control and readback, enabling automated calibration. When utilised with a CalBench system, these dry block calibrators are used as the temperature source with the UUT (sensor) output measurement via a module. Modules like the 8060, 7051 or 5065B feature precision RTD and thermocouple measurement.

Additional multi-channel signal scanners are available for batch testing of temperature devices, automated via EasyCal software. These include the 7085A 10 channel scanner module and the 8085 advanced signal multi-scanner module (8 or 16 channel versions). Both modules are also available as benchtop units.

## Features

- 7880: -100 to 155 °C (-148 to 311 °F)
- 7882: 33 to 700 °C (91 to 1292 °F)
- Excellent accuracy and stability
- Settable resolution: 1, 0.1, 0.01 ° or 0.001 °
- Simple operation and intuitive display
- Stability indicator
- Supplied with multi hole insert
- Auto stepping
- MVI Mains Variance Immunity
- EasyCal software compatible

## Specifications

Model	Temp Range	Heating Times	Cooling Times	Accuracy	Resolution	Stability	Approx Time to Stability	Immersion depth	Insert diameter
7880	-100 to 155 °C (-148 to 311 °F)	-100 to 23 °C: 12 mins 23 to 155 °C: 14 mins	155 to 23 °C: 40 mins 23 to -80 °C: 65 mins -80 to -90 °C: 20 mins -90 to -100 °C: 50 mins 155 to -100 °C: 175 mins	±0.30 °C (0.54 °F)	1 °, 0.1 °, 0.01 ° or 0.001 °C/°F	±0.03 °C (0.054 °F)	10 mins	190 mm (7.48 in.)	30 mm (1.18 in.)
7882	33 to 700 °C (91 to 1292 °F)	33 to 700 °C: 45 mins	700 to 100 °C: 43 mins 100 to 50 °C: 17 mins 50 to 33 °C: 20 mins	±0.29 °C* (0.52 °F)	1 °, 0.1 °, 0.01 ° or 0.001 °C/°F	±0.015 °C** (0.027 °F)	10 mins	200 mm (7.9 in.)	30 mm (1.18 in.)

\* Accuracy from 33 to 660 °C includes cal uncertainty. Accuracy from 660 to 700 °C is ±0.29 °C excluding cal uncertainty. 7882 is delivered calibrated from 660 to 700 °C with a cal uncertainty of ±1.4 °C \*\*7882 Full Stability Specs: 33 to 125 °C/91 to 257 °F: ±0.008 °C/±0.015 °F. 125 to 425 °C/257 to 797 °F: ±0.015 °C/±0.027 °F. 425 to 700 °C/797 to 1292 °F: ±0.02 °C/±0.036 °F.

**Supplied pre-drilled Inserts**..... Hole sizes - 7880: 3,4,4,5,6,6,9 mm & 1/4 ". 7882: 3,4,4,5,6,6,9 mm & 1/4 ".  
Imperial Versions - 7880-I: 1/8,1/4,1/4,3/16,1/4,3/8 " & 4 mm. 7882-I: 1/8,1/4,1/4,3/16,1/4,3/8 " & 4 mm.  
1 x undrilled insert supplied with each calibrator.

**Interfaces**..... USB (EasyCal compatible) and Ethernet.

**Environmental**..... Operating temperature: 0 to 40 °C (32 to 104 °F). Storage temperature: -20 to 50 °C (-4 to 122 °F). Humidity: 0 to 90 % RH.

**Mains Supply**..... 115 V AC / 60 Hz to 230 V AC / 60 Hz.

**Dimensions**..... 7880: L 531 x W 169 x H 432 mm (L 20.9 x W 6.65 x H 17.0 in). 7882: L 362 x W 171 x H 421 mm (L 14.3 x W 6.7 x H 16.6 in).

**Weight**..... 7880: 15.2kg (33.5 lb) / 7882: 11.3kg (24.9 lb)

**Supplied Accessories/Extras**..... 1 x multi hole insert, 1 x undrilled insert, carry case and traceable calibration certificate.

**Optional Extras**..... Inserts, cleaning brushes, reference probes, insulation plugs - available upon request.



## Options

### Insert Packs

Material: Inserts for the 7880: Aluminium. Inserts for the 7882: Brass.

<b>7880-METP</b> .....	Pack of 14 Metric Inserts for 7880 - 3,4,5,6,7,8,9,10,11,12,13,14,15,16 mm.
<b>7880-IMPP</b> .....	Pack of 9 Imperial Inserts for 7880 - 1/8,3/16,1/4,5/16,3/8,7/16,1/2,9/16,5/8 ".
<b>7882-METP</b> .....	Pack of 14 Metric Inserts for 7882 - 3,4,5,6,7,8,9,10,11,12,13,14,15,16 mm.
<b>7882-IMPP</b> .....	Pack of 9 Imperial Inserts for 7882 - 1/8,3/16,1/4,5/16,3/8,7/16,1/2,9/16,5/8 ".

### Reference Sensors

<b>TERS400/4/250</b> .....	PT100 reference sensor, solid with handle (-50 to 400 °C / -58 to 752 °F), diameter 4 mm (0.16 in), straight, length 250 mm (9.84 in), cable length 2m (6.6 ft), with ISO 17025 calibration certificate.
<b>TERS400/4/350</b> .....	PT100 reference sensor, solid, with handle (-50 to 400 °C / -58 to 752 °F), diameter 4 mm (0.16 in), straight, length 350 mm (13.8 in), cable length 2m (3.3 ft), with ISO 17025 calibration certificate.
<b>TERS650/4/250</b> .....	PT100 reference sensor, solid (-150 to 650 °C / -238 to 1207 °F), diameter 4 mm (0.16 in), straight, length 250 mm (9.84 in), cable length 2 m (6.6 ft), with ISO 17025 calibration certificate and carry case.
<b>TERS650/4/350</b> .....	PT100 reference sensor, solid (-150 to 650 °C / -238 to 1207 °F), diameter 4 mm (0.16 in), straight, length 350 mm (13.8 in), cable length 2 m (6.6 ft), with ISO 17025 calibration certificate and carry case.

For detailed specifications on TE reference sensors please see separate data sheet.

### EasyCal Software

<b>ECFLA</b> .....	EasyCal Calibration Software (accompanying product license).
<b>ECD-7880/82</b> .....	EasyCal software driver for dry block calibrators 7880 and 7882.

Note that a driver is included as standard when EasyCal software is purchased with a dry block calibrator or part of a turnkey package containing EasyCal. For further software options please see the EasyCal brochure.

### Additional Options

<b>ISO 17025 certificates</b> .....	C226: ISO 17025 (UKAS) calibration certificate for dry block calibrator (traceable certificate supplied as standard).
<b>Accessories upon request</b> .....	Insulation plugs, blank and pre-drilled inserts, cleaning brushes, thermal protection shields.

## Ordering Information

<b>7880</b> .....	Dry Block Calibrator (-100 to 155 °C) with metric multi hole insert, blank insert, traceable certificate & carry case
<b>7880-METP</b> .....	Pack of 14 Metric Inserts for 7880 - 3,4,5,6,7,8,9,10,11,12,13,14,15,16 mm
<b>7880-I</b> .....	Dry Block Calibrator (-100 to 155 °C) with imperial multi hole insert, blank insert, traceable certificate & carry case
<b>7880-IMPP</b> .....	Pack of 9 Imperial Inserts for 7880 - 1/8,3/16,1/4,5/16,3/8,7/16,1/2,9/16,5/8 "
<b>7882</b> .....	Dry Block Calibrator (33 to 700 °C) with metric multi hole insert, blank insert, traceable certificate & carry case
<b>7882-METP</b> .....	Pack of 14 Metric Inserts for 7882 - 3,4,5,6,7,8,9,10,11,12,13,14,15,16 mm
<b>7882-I</b> .....	Dry Block Calibrator (33 to 700 °C) with imperial multi hole insert, blank insert, traceable certificate & carry case
<b>7882-IMPP</b> .....	Pack of 9 Imperial Inserts for 7882 - 1/8,3/16,1/4,5/16,3/8,7/16,1/2,9/16,5/8 "

### Reference Sensors

<b>TERS400/4/250</b> .....	Pt100 Reference Sensor (-50 to 400 °C / -58 to 752 °F, diameter 4 mm, straight, length 250 mm)
<b>TERS400/4/350</b> .....	Pt100 Reference Sensor (-50 to 400 °C / -58 to 75 °F, diameter 4 mm, straight, length 350 mm)
<b>TERS650/4/250</b> .....	Pt100 Reference Sensor (-150 to 650 °C / -238 to 1207 °F, diameter 4 mm, length 250 mm)
<b>TERS650/4/350</b> .....	Pt100 Reference Sensor (-150 to 650 °C / -238 to 1207 °F, diameter 4 mm, length 350 mm)

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.